

## **20KD** Face and Static Seals


O-ring upgrade for static sealing


Chesterton® 20K D-ring is a continuous compression seal designed for use in static applications and is often applied as an upgrade from conventional face seals or O-ring designs. This design provides excellent performance in applications found in hydraulic or pneumatic equipment including flange and valve control units.

Each seal is individually manufactured from our unique machining process which eliminates the need for tooling costs associated with new sizes.

A continuous, high performance compression seal that is most commonly designed for use in static applications and is often applied as an upgrade from conventional O-rings. Designs are available for internal face sealing as well as external face sealing commonly found in single- or double-acting applications.

SPECIFICATIONS			$\Phi$
Material (designation)	Size Range mm (inch)	Temperature °C (°F)	Pressure Bar (psi)
AWC700 (FKM)	6 to 152 (1/4 to 6)	-30 to 200 (-20 to 400)	345 (5,000)
AWC800 (EU)	6 to 1320 (1/4 to 52)	-50 to 85 (-60 to 185)	1035 (15,000)
AWC825 (EU)	6 to 1400 (1/4 to 55)	-40 to 85 (-40 to 185)	517 (7,500)
AWC830 (EU)	6 to 254 (1/4 to 10)	-35 to 75 (-30 to 165)	517 (7,500)
AWC860 (EU)	6 to 508 (1/4 to 20)	-50 to 120 (-60 to 250)	1035 (15,000)





## PRODUCT PROFILES:













- Upgrade performance of conventional face seal and O-ring designs
- Superior wear extrusion and resistance versus conventional materials
- Low compression set characteristics
- Unique manufacturing process allows the flexibility to create any size
- Sizes made to accommodate international standards including ISO and DIN

To place an order: Product profile:	
Material:	
Rod or ram diameter (d):	
Bore diameter (D <sub>1</sub> ):	
Groove height (L):	

To place an order:	
Product profile:	_
Material:	
Piston groove diameter (d <sub>1</sub> ):	
Cylinder bore diameter (D):	
Groove height (L):	

(
_



## GLOBAL SOLUTIONS, LOCAL SERVICE

Since its founding in 1884, A.W. Chesterton Company has successfully met the critical needs of its diverse customer base. Today, as always, customers count on Chesterton solutions to increase equipment reliability, optimize energy consumption, and provide local technical support and service wherever they are in the world.

Chesterton's global capabilities include:

- Servicing plants in over 100 countries
- Global manufacturing operations
- More than 500 Service Centers and Sales Offices worldwide
- Over 1200 trained local Service Specialists and Technicians

Visit our website at www.chesterton.com

## Chesterton ISO certificates available on www.chesterton.com/corporate/iso

Technical data reflects results of laboratory tasts and is intended to indicate general characteristics only.

A.W. CHESTERTON COMPANY DISCLAMIS ALLW ARRANTIES EXPRESSED, ORIMPLED, INCLUDING WARRANTIES OF MEROHANT/ROLLTY AND FITNESS FOR A PARTICULAR PLAPOSE OR USE LUBBUTY, IF ANY, IS LIMITED TO PRODUCT REPLACEMENT ONLY.

ANY INVASES CONTAINED HEREIN ARE FOR GENERAL LILLUSTRATIVE OR AESTHETIC PURPOSES ONLY AND ARE NOT INTENDED TO CONNEY ANY INSTITUTIONAL, SAFETY, HANDIUNG OR USRGE INFORMATION OR ADVICE RESPECTING ANY PRODUCT OR
EQUIPMENT, PLEME REPERT OR ELEVANT MATERIAL SAFETYOATA SHEETS, PRODUCT COATS AFEETS AND OR PRODUCT LABELS FOR SHE USE, STOR AGE, HANDIUNG AND DEPOSAL OF PRODUCT OR CONSULT WITH YOUR LOCAL. DESTERTION REPRESENTATIVE.



DISTRIBUTED BY:

860 Salem Street Groveland, MA 01834 USA Telephone: 781-438-7000 Fax: 978-469-6528 www.chesterton.com



Sede legale: Via Panoramica 191 – 23010 Berbenno di Valtellina (SO) Sede operativa: Via Europa angolo G. Marconi sn – 23010 Berbenno di Valtellina (SO) C.F. /P. IVA: 00877330142 Tel. 0342 49 27 14 Mali: info@mkr.it – Pec: mkr@pec-legal.it