

8K and **27K** Rod and Piston Seals


Pressure sensitive, stacked set for hydraulic sealing


The Chesterton® 8K and 27K are single acting, stacked V-ring sets with a positive rake design to provide optimum operating performance. Unlike conventional stacked sets, these designs make contact through the center to ensure even loading, longer sealing life, and with minimal gland pressure. These sets are available in split or solid designs and provide excellent performance in closed-cavity hydraulic applications.

The 8K is a compression molded stacked set that utilizes tooling to create a final product. The 27K is manufactured using a machining process which allows the flexibility to create any size based on equipment dimensions and eliminates tooling cost for new sizes. Each set incorporates a male and female adapter to align and support the sealer rings.

Additional profiles have been derived from the original 8K design to address specific needs and applications in the market. These include designs for excessive clearances and deep stuffing boxes.


| SPECIFICATIONS | | | | ₫ |
|---------------------------|-------------------------|-------------------------|-----------------------|-----------------------|
| Material (designation) | Size Range mm (inch) | Temperature °C (°F) | Pressure bar (psi) | Speed m/s (ft/min) |
| AWC700 (FKM) | 6 to 152 (1/4 to 6) | -30 to 200 (-20 to 400) | 345 (5,000) | 1.5 (300) |
| AWC800 (EU) | 6 to 1320 (1/4 to 52) | -50 to 85 (-60 to 185) | 1035 (15,000) | 0.9 (185) |
| AWC805 (EU) | 6 to 1320 (1/4 to 52) | -50 to 85 (-60 to 185) | 1035 (15,000) | 0.5 (100) |
| AWC825 (EU) | 6 to 1400 (1/4 to 55) | -40 to 85 (-40 to 185) | 517 (7,500) | 0.5 (100) |
| AWC830 (EU) | 6 to 254 (1/4 to 10) | -35 to 75 (-30 to 165) | 520 (7,500) | 0.9 (185) |
| AWC860 (EU) | 6 to 508 (1/4 to 20) | -50 to 120 (-60 to 250) | 1035 (15,000) | 1.25 (250) |





PRODUCT PROFILES:





- Even stack load enables faster cycling with less friction and optimum sealing force
- Flared, pressure sensitive lip; sealing forces are reactive to pressure
- Delivered as split components for ease of installation
- Sizes made to accommodate international standards including ISO and DIN

| 0 | pΙ | а | ce | an | 0 | rd | er: | ı |
|---|----|---|----|----|---|----|-----|---|
| | | | | | | | | |

| To place all older. |
|---|
| Product profile: |
| Material: |
| Piston groove diameter (d ₁): |
| Cylinder bore diameter (D): |
| Groove height (L): |

To place an order:

| • |
|-----------------------------------|
| Product profile: |
| Material: |
| Rod or ram diameter (d): |
| Bore diameter (D ₁): |
| Working height (L ₃): |
| |



GLOBAL SOLUTIONS, LOCAL SERVICE

Since its founding in 1884, A.W. Chesterton Company has successfully met the critical needs of its diverse customer base. Today, as always, customers count on Chesterton solutions to increase equipment reliability, optimize energy consumption, and provide local technical support and service wherever they are in the world.

Chesterton's global capabilities include:

- Servicing plants in over 100 countries
- Global manufacturing operations
- More than 500 Service Centers and Sales Offices worldwide
- Over 1200 trained local Service Specialists and Technicians

Visit our website at www.chesterton.com

Chesterton ISO certificates available on www.chesterton.com/corporate/iso

Technical data-reflects results of laboratory tasts and is intended to indicate general characteristics only.

A.W. CHESTERTON COMPANY DISCLAIMS ALLW MERIANTES EXPRESSED, ORIMPLED, INCLUDING WARRANTES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PLAPOSE CRUSS LUBBILITY, IF ANY, IS LIMITED TO PRODUCT REPLACEMENT ONLY.

ANY INAGES CONTAINED HERBIN ARE FOR GENERAL ILLUSTRATIVE OR AESTHETIC PURPOSES ONLY AND ARE NOT INTENDED TO CONNEY ANY INSTRUCTIONAL, SAFETY, HANDLING OR USAGE INFORMATION OR ADMICE RESPECTING ANY PRODUCT OR
EQUIPMENT, PLEME REPERT OR RELEVANT MATERIAL SAFETY POULT ON TA SHEETS, PRODUCT CONTAINED AND ORD OSCILLATION THEY OWN LOCAL. OR STRETCH ON PERFECTION REPRESENTATIVE.



DISTRIBUTED BY:

860 Salem Street Groveland, MA 01834 USA Telephone: 781-438-7000 Fax: 978-469-6528 www.chesterton.com



Sede legale: Via Panoramica 191 – 23010 Berbenno di Valtellina (SO) Sede operativa: Via Europa angolo G. Marconi sn – 23010 Berbenno di Valtellina (SO) C.F. /P. IVA: 00877330142 Tel. 0342 49 27 14 Mali: info@mkr.it – Pec: mkr@pec-legal.it

PRINTED IN USA 7/16